Application No.: 09/993,820

.. 0*01005*,020

Status of the claims:

(Herein Amended) In combination a releasable tube holder and a longitudinal support

comprising,

said tubular holder including a circular plastic tube split lengthwise into longitudinally

mirror image straight halves forming two opposed clamping members joined together at across a

first pair of split edges and separated by a second pair split edges, each clamping member

provided with at least one separated handle member positioned on one of the clamping member

halves and opposite another handle member on the other clamping member half, said clamping

member halves being identical in cross-section and together forming a cylindrical surface being

hingedly connected by a living hinge formed by a groove between said first pair of split edges to

activate opening and closing of the opposed clamping members and separation and closing of the

second pair of split edges which engage and are secured to the support by applying and removing

pressure on the oppositely positioned handle members.

2. (Herein Amended) In combination a releasable tube holder and a longitudinal support

comprising,

said longitudinal support supporting a towel hanging therefrom,

said tubular holder including a circular plastic tube split lengthwise into longitudinally mirror

image straight halves forming two opposed clamping members joined together at across a first

pair of split edges and separated by a second pair of split edges, each clamping member provided

with at least one separated handle member positioned on one of the clamping member halves and

opposite another handle member on the other clamping member half, said clamping member

halves being identical in cross-section and together forming a cylindrical surface being hingedly

2

Application No.: 09/993,820

d: 11/16/2001

connected by a living hinge formed by a groove between said first pair of split edges to activate

opening and closing of the opposed clamping members and separation and closing of the second

pair of split edges which engage and are secured to the support by applying and removing

pressure on the oppositely positioned handle members.

6. (Allowed) In combination a releasable tube holder and a longitudinal support comprising,

said tubular holder including a circular plastic tube split lengthwise into longitudinally

mirror image straight halves forming two opposed clamping members joined together at across a

first pair of split edges and separated by a second pair of split edges, each clamping member

provided with at least one separated handle member positioned on one of the clamping member

halves and opposite another handle member on the other clamping member half, said clamping

member halves being hingedly interconnected with a hinge pin connected by a hinge on each

clamping member half said first pair of split edges with a torsion spring positioned between said

first pair of split edges of said clamping member halves to activate opening and closing of the

opposed clamping members and separation and closing of the second pair of split edges which

engage and are secured to the support by applying and removing pressure on the oppositely

positioned handle members.

· 3

Application No.: 09/993,820

Filed: 11/16/2001

(Herein Amended) In combination, a releasable tube holder and a longitudinal support

comprising,

said tube holder including a circular plastic tube split lengthwise longitudinally into

mirror image straight halves being identical in cross-section and together forming a cylindrical

surface forming two opposed clamping members joined together at a first pair of straight across

split edges and separated by a second pair of split edges, each clamping member provided with at

least one separated handle member positioned on one of the clamping members and opposite

another handle member on the other clamping member, said clamping member being hingedly

connected by a living hinge member formed by a groove along one pair of said first pair of split

edges to activate opening and closing of the opposed clamping members and separation and

closing of said second pair of split edges which engage and are secured to the support by

applying and removing pressure on the oppositely positioned handle members.

8. (Previously Amended). The holder of claim 7 wherein said living hinge member extends

along and in the direction of said one pair of straight across split edges hingedly connected by

said living hinge member extending along the axis of the first pair of split edges.

9. (Herein Canceled).

10. (Previously Canceled).

4